

ONE STOP PERMIT

Permit Issued By:
 Tama County Hwy. Dept.
 1002 East 5th Street
 Tama, IA 52339
 P: 641-484-3341 F: 641-484-6628

Permit No. _____

- Single Trip \$ _____
 Annual Oversize \$ _____
 Round Trip \$ _____

(Return by reverse route within same 5 days)

Section A – Issue to:							
Legal Name – Vehicle Owner or Lessee		Date		Requested by			
Address		City		State ZIP Code			
Email address		Phone Number		FAX Number			
Section B – Load – Describe Article(s) Transported		Serial No.		Model Number			
S.M.E. Plate No.		<input type="checkbox"/> Towaway <input type="checkbox"/> Self-Propelled					
Section C – Power Unit & Trailer Information							
Power Unit License No. & State		Power Unit Year & Make		Vehicle Identification No. (VIN)			
Power Unit Registered Weight		Trailer License No. & State		Trailer Make			
Section D – Dimensions/Weight							
	Overall	Trailer	Load	Front Projection	Rear Projection		
Length							
Width							
Height							
Gross Weight							
Section E – Axle Weights/Spacing – front to rear (required when gross weight exceeds 80,000 lbs)							
Axle Number Gross Axle Weight (lbs)	1 (front)	2	3	4	5	6	7
Axle Spacing							
Axle Number Gross Axle Weight (lbs)	8	9	10	11	12	13	14
Axle Spacing							
Section F - Trip							
Coming From			Going To				
Route							
Valid Dates			<input type="checkbox"/> 1/2 hr before sunrise to 1/2 after sunset		<input type="checkbox"/> Continous		
Section G – Permit Delivery (check one)							
<input type="checkbox"/> Mailing address			Acceptance of Conditions: I certify that the statements contained In the application are true and correct, and I will comply with the General Provisions dated 06-2008. X				
<input type="checkbox"/> Fax <input type="checkbox"/> Email							
X							
Issued by Tama County Hwy Dept.		Date		Customer or Authorized Agent Date			
<input type="checkbox"/> Centerline all bridges at 5 mph. Load must slow or stop when necessary to avoid approaching traffic when centerlining.							
<input type="checkbox"/> Special Requirements							

Please allow one business day, prior to the date of move, to process this permit.
 Thank you

IOWA GENERAL PROVISIONS FOR OVERSIZE LOAD PERMIT

The State of Iowa, the Iowa Department of Transportation and any other permit issuing authority assume no responsibility for the property of the permit holder. During movement under permit, the permit holder must meet the terms and conditions of the permit and must take all reasonable precautions to protect and safeguard the lives and property of the traveling public and adjacent property owners. A copy of a current certificate of public liability insurance in the amounts of \$100,000 bodily injury each person, \$200,000 bodily injury each occurrence, and \$50,000 property damage must be carried in the vehicle for which the permit has been issued. Nothing shall exempt the permit holder from compliance with any load limitations which have been or might be established on any bridge or road that is posted with embargo signs. The permit and any revisions will be void if the actual weights or dimensions exceed what is indicated on the permit or its revisions. Permits can be issued only for loads that are a single article that cannot be reasonably broken down to make it legal in size and weight. The permit must be carried in the cab of the vehicle for which it has been issued and be available for inspection.

Movement is allowed seven days a week except for designated holidays and for special events when abnormally high traffic counts can be expected. The designated holidays are: Memorial Day, Independence Day, and Labor Day. No movement will be allowed on these holidays or after 12 noon on days preceding these holidays and holiday weekends which include holidays that fall on Monday, except as provided for in Section 321.457 of the Code.

Any reportable accident involving a vehicle operating under permit must be reported in writing to the Director of the Office of Vehicle & Motor Carrier Services, P.O. Box 10382, Des Moines, IA 50306-0382.

Escort Requirements- Escorts must be at least 18 years old, possess a valid Class A, B, C or D driver's license, and carry proof of public liability insurance in the amounts of \$100,000/\$200,000/\$50,000. The escort vehicle must be approximately the size of a normal passenger automobile or pickup and must have an amber revolving light. The light must be at least 7" high and 7" in diameter, with at least a 100-candlepower lamp providing 360° warning (or a strobe light), and be mounted on top of the escort vehicle which must be burning while escorting a permit load. An 18" square red flag must be on each corner of the front bumper of the vehicle.

- A rear escort is required when vehicle length exceeds 120 feet.
- A rear escort is required when the width of the vehicle and load is over 16 feet 6 inches and travel is on 4 lane roadways.
- A rear escort or an amber light or strobe light on the power unit and on the rear extremity of the vehicle or load when width exceeds one-half the roadway up to and including 16 feet 6 inches and travel is on 4 lane roadways.
- A front escort is required when: Width is up to and including 14 feet 6 inches and exceeds one-half the roadway and travel is on 2 lane roadways with lane width less than 12 feet OR Width is up to and including 14 feet 6 inches and exceeds one-half the roadway and travel is on 2 lane roadways with lane width 12 feet or more without sufficient shoulders OR Width is over 14 feet 6 inches and travel is on 2 lane roadways.
- A front escort- or an amber light or strobe light on the power unit and on the rear extremity of the vehicle or load, when width is up to and including 14 feet 6 inches and exceeds one-half the roadway and travel is on 2 lane roadways with lane width 12 feet or more with sufficient shoulders.
- A front escort with mounted height pole is required when height exceeds 14 feet 6 inches up to and including 20 feet. An escort but no height pole is required after 20 feet.

Lighting Requirements- An amber revolving light at least 7 inch high and 7 inch in diameter with at least a 100-candlepower lamp providing 360 degree warning (or strobe light) visible from front and rear, mounted on the towing unit is required when: Length exceeds 85 feet up to and including 120 feet OR Front-end projection exceeds 25 feet OR Rear-end projection exceeds 10 feet OR Weight exceeds 80,000 pounds. An escort can be used in lieu of amber light.

Signs and Flags- Signs and flags are required when a vehicle and load exceeds 75 feet in length, 8 feet 6 inches in width, and/or 14 feet 4 inches in height. In addition flags are required when the vehicle rear projection exceeds 4 feet. A sign reading "Oversize Load" must be at least 18 inches high by 7 feet long with a minimum of 12 inch black letters with a 1-1/2 inch stroke, on a yellow background, and mounted on the front bumper and on the rear of the load. A rear sign for mobile homes must be mounted at least 7 feet above the highway surface, measuring from the bottom of the sign. Flags must be red or orange fluorescent and at least 18 inches square must be mounted as follows: one flag at each front corner of the towing unit and one flag at each rear corner of the load. In addition, there must be a flag at any additional protrusion in the width of the load. The signs or warning devices must be mounted so they can be removed or covered when the vehicle is within legal dimensions.

Definition of sufficient shoulder- A gravel or paved surface extending a minimum of 6 feet beyond the edge of the roadway.

Requirements for Continuous Moves- Vehicles and loads may travel by permit between 1/2 hour after sunset and 1/2 hour before sunrise if, in addition to the general provisions and general requirements specified by the permit, the following conditions are met.

- a. Dimensions shall not exceed:
 - (1) Width. 11 feet.
 - (2) Height. 14 feet, 6 inches.
 - (3) Length. 100 feet.
 - (4) Weight. Permitted axle limits.
- b. Travel must be on roadways with a minimum width of 22 feet and minimum lane width of 11 feet.
- c. Safety lighting shall be provided at the widest part of a load. The lamps may be placed at the outer ends of the load itself or on appurtenances which are equal in width to the widest part of the load and positioned at both extreme front and rear of the vehicle or trailer as follows:
 - (1) One lighted red lamp on each side at the rear of the load.
 - (2) One lighted yellow or amber lamp on each side at the front of the load.

Telephone number for more information (515) 237-3264.